



Oil & Gear Lube Capacity Charts

UDOR-LUBE

SAE 40W Hydraulic Lubricant specially formulated for use in diaphragm & plunger pumps.

- Non-Detergent
- Non-Foaming
- Anti-Wear Agents
- Rust Inhibitors
- Resists Breakdown Due to Oxidation

Superior Lubrication

Diaphragm Pumps

Change oil and diaphragms at the end of each spray season or after 500 hours of use.

Plunger Pumps

Change oil and seal kit at the end of each spray season or after 500 hours of use.

OIL CAPACITY	
DIAPHRAGM PUMP	
IOTA 17/20	7 oz.
KAPPA 7/15/18	4 oz.
KAPPA 25	12 oz.
KAPPA 30/40	20 oz.
KAPPA 33/43/53	20 oz.
KAPPA 35/55	23 oz.
KAPPA 75	30 oz.
KAPPA 100	40 oz.
KAPPA 120/150	84 oz.
OMEGA 140/170	87 oz.
RO 70	18 oz.
RO 106/110/121/125/130	30 oz.
RO 160/175	44 oz.
RO 210/250	90 oz.
RO 320	160 oz.
ZETA 40/85/100	32 oz.
BETA 110/150	87 oz.
BETA 200/240	160 oz.
PLUNGER PUMP	
P SERIES	12 oz.
M SERIES	20 oz.
MK SERIES	28 oz.
G SERIES	40 oz.
GHC SERIES	40 oz.
GK SERIES	40 oz.
GAMMA 60/62	44 oz.
GAMMA 75/95/100	84 oz.
GAMMA 162/200/202/242	89 oz.
GAMMA-V SERIES	84 oz.
PENTA SERIES	80 oz.
NX SERIES	44 oz.

GEAR LUBE CAPACITY	
DIAPHRAGM PUMP GEAR BOXES	
5027.75	16 oz.
5028.76	3 oz.
5033.A4	16 oz.
5034.B5	28 oz.
5035.74	2 oz.
5047.D7	2 oz.
5050.E2	3 oz.
5085.F7	3 oz.
5091.D9	3 oz.
5094.76	3 oz.
5096.B5	28 oz.
PLUNGER PUMP GEAR BOXES	
5038.C2	10 oz.
5042.C2	10 oz.
5053.E5	16 oz.
5055.E7	6 oz.
5062.C2	10 oz.
5063.B5	28 oz.