



CaviBlaster Crawler

Gasoline Engine, 12 gpm & 2,800 psi

Specifications and Options

Our most popular commercial unit, is a compact and lightweight system with superior cleaning performance utilizing the Ultra-Cavitation technology

Accessories Included:

Feed Hose (15 feet) with electric suction pump, By-Pass Hose (15 feet), High Pressure Hose (50 feet), Zero-Thrust Balanced Gun, Battery Start

Optional Accessories:

Additional pressure hose available in 50 ft or 100 ft sections
Max. Pressure hose length recommended up to 300 ft (100 meters) total



SKID Dimensions

Length w/o handle	35" / 89 cm
Length w handle	45" / 114 cm
Width	26" / 66 cm
Height	29" / 74 cm
Weight	280 Lbs / 127 Kg

Pump System

Pressure Pump	General TSF 2421 Plus
Pump Material / Type	Triplex Plunger - Brass
Flow Rate	12 gpm / 45 Lpm
Pressure	2,800 psi / 193 Bar
Hose Diam/Max Lgth	1/2" - 300 ft / 100 meters

Shipping Dimensions

Pallet 48x40x36"	500 Lbs / 226 Kgs
------------------	-------------------

Drive System

Engine	Honda iGX800
Engine Type	2-cylinder air-cooled
Intake System	Naturally aspirated
Combustion System	Electronic Fuel Injection
Power Output Max	28 HP / 21 kW
Power Output Cont.	24 HP / 18 kW
Clutch Type	None
Starting System	Electric

Feed System

Feed Pump	Johnson L2200
Pump Material	Thermoplastic, SS Shaft
Flow Rate @ Max Lift	29gpm/110L/m @ 3.3Lft/1m
Pump Power supply	12V @ 7.5Amp

Ideal For

Boat Hulls
Barges
Flat Metallic Surfaces

Tool Options

Zero-Thrust Balanced Gun
Double Un-Balanced Guns
Single CaviDome
ROV Lance
Autonomous hull cleaner

* Pricing and specifications subject to change without notice

